




Technical Details

EXTERNAL SHELL: P.P. Polypropylene
 INTERNAL SHELL: HD Polystyrene expanded
 HEADBAND: Soft PA Nylon headband
 (fixed to the external shell without metal rivets)
 SIZE: Universal-adjustable from 51 to 63 cm
 STANDARD: EN 397

 390 g  -30°C / +50°C

 * Protection against side, front and rear impacts in conformity with the requirements of the EN 12492



WHE00008.201
WHITE



WHE00008.202
YELLOW



WHE00008.203
ORANGE



WHE00008.204
RED



WHE00008.205
GREEN



WHE00008.206
BRITISH GREEN



WHE00008.207
ROYAL



WHE00008.208
BLUE



WHE00008.210
BLACK

Technology



AIR

VENTILATION: Maximum ventilation thanks to the ten air intakes. The air intakes and the internal outflow channels guarantee effective breathability.



CLIP

LAMP CLIPS: Helmet equipped with strong nylon external lamp carrying clips, made of high intensity resin and frontal antislid insert that are compatible with all headlamps with elastic bands on the market.



GRID

ANTI-INTRUSION GRILLE: The air intakes are equipped with an anti-intrusion grille that prevents entry of debris whilst maintaining breathability.



CHINSTRAP
EN 397

CHINSTRAP EN 397: Four point chinstrap fixed to the external shell without metal rivets with Quick release fastening and opening in conformity with EN 397. Provided with lateral divider for adjusting the length of the straps.



RING TO HOOK

RING TO HOOK: Fitted with a special loop on the chinstrap which allows the helmet to be connected to the harness.



2DRY

2DRY: This high-tech and maximum comfort fabric dries very quickly, encouraging the expansion and dispersion of moisture to the outside and leaving a pleasant feeling of freshness.



MICROMETRICAL ADJUSTMENT: The micrometric size regulation mechanism positioned at the rear of the helmet provides quick and precise adjustment, even when wearing gloves.



VISOR









VISOR ATTACHMENT: Provided with attachment for fitting visors.




EARMUFFS


EARMUFFS FITTING: Provided with bayonet socket adapter for earmuffs. Compatible with KASK earmuffs.


Performances

| | |
|---|--|
| PROTECTION AGAINST TOP IMPACTS |  5 Kg from 2 m 100 J |
| PROTECTION AGAINST SIDE, FRONT AND REAR IMPACTS |  5 Kg from 0,5 m 25 J |
| PROTECTION AGAINST THE PENETRATION OF OBJECTS |  3 Kg from 1 m 30 J |
| CHIN STRAP RELEASE > 15 kg <25 kg |  |
| RETENTION SYSTEM EFFECTIVENESS |  |
| LOWER TEMPERATURE RESISTANCE TEST |  T= -30°C |
| PROTECTION AGAINST SIDE DEFORMATION- LD |  |
| PROTECTION AGAINST MOLTEN METAL SPLASHES- MM |  |



 Standard requirements

 Additional test in conformity with the requirements of the EN 12492

 Optional requirements

Additional Information



GUARANTEE

3 years starting from the purchasing date.

SHELF LIFE

10 years starting from the production date (production date is printed on a label contained on the inside of the helmet).

Inspect the helmet regularly to check for any damage! Cuts, abrasions, deformation or changes in colour represent important elements for checking the helmet status.

CLEANING

Clean the helmet only with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). Do not use chemical detergent or solvent.

STORAGE

When not in use the helmet should be stored away from direct sunlight or source of heat.

ADHESIVE APPLICATION

Do not apply adhesives, solvents, stickers or paint that do not comply with the manufacturer's specifications. Any alteration or intervention not provided for may impair its protective function.

Accessories



WV100018
Visor V2 Plus



WV100003
Visor FULL FACE



WV100006
Mesh visor



WAC00003
Adapter for earmuffs



WPA00002
Inner padding



WAC00008
Visor carrier 30 mm
attachment



WV100005
Mesh visor carrier



WHP00004/5/6
Earmuffs



WAC00026
Helmet bag



WPA00007
Winter padding



WAC00020
Neck Shade



WAC00024
Neck Shade HI VIZ