



Technical Details

EXTERNAL SHELL: P.P. Polypropylene
INTERNAL SHELL: HD Polystyrene
HEADBAND: Soft PA Nylon
(fixed to the external shell without metal rivets)
SIZE: Universal-adjustable from 51 to 62 cm
STANDARD: EN 12492

 420 g  -20°C / +35°C



AHE00005.201
WHITE



AHE00005.202
YELLOW



AHE00005.203
ORANGE



AHE00005.204
RED



AHE00005.208
BLUE



AHE00005.209
ANTRACITE



AHE00005.210
BLACK

Technology



AIR

VENTILATION: Maximum ventilation thanks to the ten air intakes. The air intakes and the internal outflow channels guarantee effective breathability.



CLIP

LAMP CLIPS: Helmet is equipped with strong external carrying clips, made of high intensity resin and frontal antislid insert that are compatible with all headlamps with elastic bands on the market.



GRID

ANTI-INTRUSION GRILLE: The air intakes are equipped with an anti-intrusion grille that prevents entry of debris whilst maintaining breathability.



CHINSTRAP
EN 12492

CHINSTRAP EN 12492: Four point chinstrap with which is crossed at the back to secure the helmet to the head better. The safety release system allows quick fastening and opening of the locking mechanism in conformity with EN 12492. Provided with lateral divider for adjusting the length of the straps.



RING TO HOOK

RING TO HOOK: Fitted with a special hook on the chinstrap which allows the helmet to be connected to the harness.



2DRY

2DRY: This high-tech and maximum comfort fabric dries very quickly, encouraging the expansion and dispersion of moisture to the outside and leaving a pleasant feeling.



UP&DOWN

UP & DOWN SYSTEM: The innovative and exclusive UP & Down technology ensures a precise and comfortable fit around the neck. A center wheel and two side flaps allow quick adjustment of the helmet not only in width but also in height and tilt.



VISOR

VISOR ATTACHMENT: Provided with attachment for fitting visors.



EARMUFFS

EARMUFFS FITTING: Built with bayonet adapter for earmuffs. Compatible with KASK earmuffs.

Performances

PROTECTION AGAINST TOP IMPACTS		5 Kg from 2 m 100 J
PROTECTION AGAINST SIDE, FRONT AND REAR IMPACTS		5 Kg from 0,5 m 25 J
PROTECTION AGAINST THE PENETRATION OF OBJECTS		3 Kg from 1 m 30 J
CHIN STRAP RESISTANCE > 50 KG		
RETENTION SYSTEM EFFECTIVENESS		

 Standard requirements



Additional Information



GUARANTEE

3 years starting from the purchasing date.

SHELF LIFE

10 years starting from the production date (production date is printed on a label contained on the inside of the helmet).

Inspect the helmet regularly to check for any damage! Cuts, abrasions, deformation or changes in colour represent important elements for checking the helmet status.

CLEANING

Clean the helmet only with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). Do not use chemical detergent or solvent.

STORAGE

When not in use the helmet should be stored away from direct sunlight or source of heat.

ADHESIVE APPLICATION

Do not apply adhesives, solvents, stickers or paint that do not comply with the manufacturer's specifications. Any alteration or intervention not provided for may impair its protective function.

Accessories



WV100018
Visor V2 Plus



WV100003
Visor FULL FACE



WV100006
Mesh visor



WAC00003
Adapter for earmuffs



WPA00002
Inner padding



WAC00008
Visor carrier 30 mm attachment



WV100005
Mesh visor carrier



WHP00004/5/6
Earmuffs



WAC00026
Helmet bag



WPA00007
Winter padding



WAC00020
Neck Shade



WAC00024
Neck Shade HI VIZ